



Deep Cycle/Industrial Battery Applications

Model	Volts	Ah		CCA	RC 25A	RC 75A	Dimensions (in.)			Terminals Available	Weight (lb.)		# of Plates	Cover/Case Color	Pallet Quantity
		20 Hr.					L	W	H		Wet	Dry			
Aircraft															
UAC25	12	35	235	35	–	7.71	5.18	7.53	T	26	–	54	Red/Gray	84	
UAC35	12	42	330	45	–	9.78	5.17	7.23	T	35	–	78	Red/Gray	84	
Floor Machine (Sweeper, Scrubber)															
U2500	6	250	–	540	150	11.62	7.12	11.63	SL	72	59	63	Black/Black	36	
U2500HC	6	275	–	600	168	11.62	7.12	11.63	SL	78	61	69	Navy/Navy	36	
U3050	6	305	–	675	175	11.88	7.12	15.00	SL	87	71	57	Black/Black	18	
U3050HC	6	335	–	747	203	11.88	7.12	15.00	SL	96	78	63	Navy/Navy	18	
UL16	6	375	–	810	214	11.88	7.12	17.00	LS	111	89	51	Black/Black	18	
UL16HC	6	415	–	890	236	11.88	7.12	17.00	LS	117	95	57	Navy/Navy	18	
U1450	12	145	–	270	72	13.62	6.75	12.25	LA	87	71	78	Black/Black	36	
U1850	12	195	–	375	100	15.50	7.06	14.25	SL	111	90	66	Black/Black	14	
U1850HC	12	215	–	418	110	15.50	7.06	14.25	SL	116	96	78	Navy/Navy	14	
Golf Car															
UAGC2	6	220	–	492	–	10.38	7.13	11.19	L	66	–	–	Gray/Gray	48	
U2000	6	210	–	420	108	10.25	7.12	11.12	US	59	48	45	Black/Black	48	
U2200	6	225	–	447	115	10.25	7.12	11.12	US	63	51	57	Gray/White	48	
U2300	6	235	–	448	132	10.25	7.12	11.12	US	67	55	63	Green/White	48	
U2400	6	244	–	530	145	10.25	7.12	11.88	US	70	60	57	Blue/White	48	
U8VGC	8	165	–	318	85	10.25	7.12	11.33	US	65	53	60	Red/White	48	
Marine															
USRM8V19	8	142	600	305	92	19.25	7.50	10.75	L	93	76	100	Rubber (Black)	24	
USRM8V21	8	155	715	330	98	21.44	7.50	10.50	L	103	84	108	Rubber (Black)	24	
USRM8V24	8	190	880	430	134	24.38	7.44	10.50	L	118	96	132	Rubber (Black)	16	
USRM8V27	8	215	1000	445	122	27.44	7.44	10.50	L	132	108	148	Rubber (Black)	16	
USRM8V26	8	240	1050	515	145	26.75	8.44	11.12	L	149	121	156	Rubber (Black)	16	
Multi-Purpose Deep Cycle															
USRM1	6	95	–	165	44	9.13	7.13	9.38	SA	30	24	45	Black/Black	72	
USRMU1	12	35	–	55	15	8.19	5.19	7.12	L	21	18	60	Red/White	120	
USRM22NF	12	60	–	108	31	9.44	5.50	9.00	SA	34	28	66	Red/White	84	
USRM22F	12	65	–	98	24	9.50	6.56	8.31	S	35	29	66	Black/White	72	
USRM78	12	70	–	122	34	10.25	7.06	8.00	I	43	35	78	Black/Black	72	
UBIGJOE	12	107	–	185	48	18.00	7.25	9.63	AS	80	65	102	Rubber (Black)	28	
USRM16TF	12	120	–	250	74	16.56	7.12	11.12	SA	91	74	66	Rubber (Black)	28	
USRM8D	12	240	–	455	106	20.75	11.12	9.88	SAL	127	104	174	Black/Black	16	

Model	Volts	Ah		RC		Dimensions (in.)			Terminals Available	Weight (lb.)			# of Plates	Cover/Case Color	Pallet Quantity
		20 Hr.	CCA	25A	75A	L	W	H		Wet	Dry				
Starting															
U17HF-50	6	—	360	115	—	7.38	6.88	9.25	A	26	21	39	Rubber (Black)	90	
U19L-50	6	—	525	110	—	8.19	6.69	7.44	A	26	21	39	Rubber (Black)	90	
U2E-VHD	6	—	600	180	—	19.38	4.12	9.12	A	38	31	45	Rubber (Black)	60	
U2N-VHD	6	—	625	200	—	10.00	5.56	9.00	A	36	29	51	Rubber (Black)	84	
U2-XHD	6	—	675	185	—	10.38	7.12	9.38	A	35	29	51	Black/Black	72	
U4-RD	6	—	860	240	—	13.13	7.13	9.38	A	44	36	63	Black/Black	54	
U3EH-VHD	6	—	875	300	—	19.31	4.19	9.81	A	47	38	69	Black/Black	60	
U4-XHD	6	—	1000	320	—	13.13	7.13	9.38	A	50	41	75	Black/Black	54	
U4EH-VHD	6	—	1000	325	—	19.31	5.00	9.81	A	61	50	81	Rubber (Black)	48	
U1-8V-VHD	8	—	400	140	—	8.88	6.81	8.50	A	38	31	52	Rubber (Black)	72	
U2-8V-VHD	8	—	500	140	—	10.38	6.94	9.06	A	44	36	60	Rubber (Black)	72	
U911-50	12	—	300	65	—	8.19	6.88	6.88	A	28	23	54	Red/White	90	
U53K-VHD	12	—	360	80	—	12.75	4.62	8.94	A	35	29	54	Rubber (Black)	90	
U26-VHD	12	—	450	65	—	8.19	6.81	8.00	SU	28	23	54	Black/Black	90	
U3EE-VHD	12	—	450	100	—	19.31	4.19	8.88	A	40	33	60	Black/Black	60	
U3ET-VHD	12	—	500	140	—	19.31	4.38	9.88	A	50	41	66	Black/Black	60	
U27-50	12	—	525	120	—	12.06	6.81	8.88	A	46	37	78	Black/Black	54	
U60K-VHD	12	—	550	126	—	13.06	6.19	8.88	A	50	41	66	Rubber (Black)	54	
U17TF-VHD	12	—	625	150	—	17.06	6.94	8.00	A	61	50	102	Rubber (Black)	42	
U6TL	12	—	825	215	—	11.88	10.50	11.88	A	69	56	138	Olive/Olive	32	
U8D-1075	12	—	1100	290	—	20.75	11.12	9.88	BCL	112	92	138	Black/Black	16	
U8D-1400	12	—	1450	400	—	20.75	11.12	9.88	BCL	129	105	186	Black/Black	16	
U16V24	16	—	550	70	—	10.08	6.38	8.79	A	42	—	72	Red/Red	—	
U16V324	16	—	550	70	—	10.08	6.38	8.79	A	42	—	72	Red/Red	—	
U4HN	24	—	235	28	—	10.25	5.25	9.00	A	—	28	—	Black/Black	—	

Notes:

"Weight, Dry": A dry battery ships without electrolyte. Most are actually 'hibernated' (moist). Dry batteries are available only with standard terminals.

"Speed Caps[®]" are standard equipment on Golf Car batteries. (UAGC2 is a sealed battery and has no caps.)

Terminals: For each battery, standard terminal is listed first.

Code	Terminal Description	Fractions and Decimal Equivalents			
		Fraction	Decimal	Fraction	Decimal
A	Auto Post	1/16	0.06	9/16	0.56
B	Bus (3/8" threaded studs)	1/8	0.12	5/8	0.62
C	Bus (1/2" pos. stud, 3/8" neg. stud)	3/16	0.19	11/16	0.69
I	Threaded side insert-tube	1/4	0.25	3/4	0.75
L	L-shaped bracket with hole	5/16	0.31	13/16	0.81
S	Auto post with horizontal hole	3/8	0.38	7/8	0.88
T	Threaded stud	7/16	0.44	15/16	0.94
U	Threaded stud over auto post	1/2	0.50		