

PS600

"The World's Most Economical Solar Pump"

LORENTZ



RELIABLE AND MAINTENANCE-FREE

PS600 eliminates the weakest links in solar pumping by using helical rotor (progressive cavity) and centrifugal pump ends and a brushless and water-filled motor.

No failure-prone diaphragms, no flooded-motor failures and no electronics in the well !

- Lift from as deep as 600 ft (230 m)
- Maximum 20,000 gallons per day (100 m³)
- PS600 eliminates the costs of fuel, delivery, engine maintenance, and pollution.
- In many cases it COSTS LESS than a conventional pump and generator installation
- Great reliability and life expectancy
- High resistance to sand and corrosion
- Fits 4" and larger well casings
- Wide voltage range for 48 to 72V systems (4-6 solar modules in series) Only one controller for solar direct or battery systems

>> DEEP WELL APPLICATIONS

The pump can be submersed as deep as necessary. Submersion depth does not affect the performance or place additional stress on the pump or motor.

>> SURFACE WATER APPLICATIONS

The pump can be installed in a stream, pond, tank or shallow well, in any position.

>> DRY RUN PROTECTION

An optional low water probe turns pump off to prevent dry-run damage. Reset is automatic after 20 minutes. The PS600 Controller has an RPM limit adjustment to reduce the maximum flow rate to about 50 %, to help match a limited water source.

>> SAND AND SILT TOLERANCE

The pump has high resistance to wear from sand, clay, etc. that may occur in a properly constructed water well. However, a concentration of solids greater than 2 % (by volume) may cause blockage in the pump or the drop pipe, especially at low flow rates. Do not use the pump to clean out a dirty well.

>> CONTROLLER

MPPT, well probe and float-remote switch terminals
Lights indicate: system on, pump on, pump speed, tank full, water source low, overload, and battery low. Protected against reverse polarity, overload and high temperature.

>> BATTERY SYSTEMS

LOW-VOLTAGE DISCONNECT prevents battery damage from over-discharge. This feature is included in the controller.
Disconnect - Reconnect 44V-52V

>> STORAGE REQUIREMENT

A storage tank (not included) should be sized to supply a minimum of 5-10 days' water supply, depending on climate and application. Water storage is generally more economical than energy storage in batteries.

>> DROP PIPE

1" NPT pump outlet on 07, 04, 04H and 03H. 1 1/4" NPT on 20 and 14.
If water is dirty, consider a smaller size drop pipe to increase the flow velocity. This helps exhaust solid particles and prevent accumulation in the pipe. When considering reduced pipe size, consult a pipe sizing (friction loss) chart. Pipe can be of any standard material, rigid or flexible. A torque arrestor is NOT required.

>> PUMP CABLE and SPLICE

Standard submersible cable, 3-wire + ground (total 4 wires). Connection to the pump is made using industry-standard splicing methods.

>> DIMENSIONS & WEIGHTS

PUMP & MOTOR

- Diameter: 3.78" (96 mm)
- Height: 20" - 32" (500-800 mm) depending on model
- Weight: 25 lbs (11.5 kg) or less, depending on model

CONTROLLER

- Controller: 17" x 7" x 6" (425 x 175 x 150 mm)
- 3 conduit holes: 1/2", 3/4", and 1 1/4" KO
- Weight: 11 lbs (4.8 kg)
- Enclosure: gasket-sealed, weatherproof

>> WETTED MATERIALS

316 stainless steel, chromium, NBR rubber, natural rubber, POM, polyurethane (cable)

>> TEMPERATURE LIMITS

- Pump: Specify Temperature Class on order
 - Class 1 46° F to 72° F
 - Class 2 64° F to 90° F
 - Class 3 82° F to 104° F
- Controller: Ambient -22° to 131° F (-30° C to 55° C)



>> NEED MORE WATER ?

Consider the PS1200 system. This systems use more power, to pump as high as 750 ft (230m) and as much as 25,000 gallons per day.

>> INSTALLATION

Install the pump by the same methods and materials used for conventional submersible pumps. The PS600 instruction manual is clearly illustrated. No special product training is required.

>> OPTIONAL EQUIPMENT:

- Low-water probe
- 4 wire submersible cable splice kit, 3 wire + ground
- Disconnect and Junction box

>> TWO YEAR MANUFACTURER'S WARRANTY

against defects in materials and workmanship.

PS600 SIZING TABLE for Solar Direct Systems

Ver: 05/01/10

Fixed and single axis tracked Systems



VERTICAL LIFT	16 Feet 5m		33 Feet 10m		50 Feet 15m		65 Feet 20m		100 Feet 30m		133 Feet 40m		165 Feet 50m		200 Feet 60m		230 Feet 70m	
	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked

US Gallons x 1000 / day

PEAK	7.5	9.25	13.21	5.00	7.13	5.00	6.87	3.96	5.71	1.98	2.51	1.64	2.30	1.59	2.09	1.24	1.80	1.00	1.40
SUN	6.0	7.93	11.10	4.09	5.71	3.95	5.41	2.91	4.11	1.65	2.16	1.42	1.95	1.26	1.67	0.99	1.40	0.80	1.10
hours/day	4.5	6.60	8.98	3.17	4.28	2.90	3.94	1.85	2.50	1.32	1.80	1.19	1.59	0.92	1.24	0.74	1.00	0.60	0.80
300 Wp	C-BF-04		HR-14						HR-04						HR-03				
GPM	21.0		12.3		10.6		9.5		3.6		3.5		3.3		2.9		1.8		
Wire size / max. length	#10 / 150ft																		

PEAK	7.5	11.1	16.1	5.8	7.9	6.0	7.7	4.7	6.9	3.7	5.3	1.8	2.3	1.6	2.2	1.5	2.1	1.3	1.8
SUN	6.0	9.8	14.0	5.0	6.9	4.8	6.3	4.0	5.2	2.6	3.7	1.7	2.2	1.5	2.0	1.3	1.8	1.1	1.5
hours/day	4.5	8.5	11.6	4.2	5.8	3.7	5.0	2.6	3.6	1.6	2.1	1.6	2.1	1.2	1.6	1.1	1.5	0.9	1.3
350 Wp	C-BF-04		HR-14						HR-04										
GPM	21.0		12.3		10.6		9.5		7.9		3.5		3.3		2.9		2.6		
Wire size / max. length	#10 / 150ft																		

PEAK	7.5	12.4	18.0	6.9	8.3	6.3	8.0	5.3	7.7	4.2	6.1	2.3	3.3	1.8	2.3	1.6	2.2	1.5	2.0
SUN	6.0	11.0	15.5	5.8	7.1	5.2	6.7	4.5	6.3	3.2	4.5	2.0	2.8	1.6	2.1	1.4	1.9	1.3	1.7
hours/day	4.5	9.5	13.0	4.6	6.2	4.0	5.4	3.7	5.0	2.1	2.9	1.7	2.3	1.3	1.9	1.2	1.6	1.1	1.4
420 Wp	C-BF-04		HR-14						HR-07		HR-04								
GPM	23.0		11.4		11.0		10.0		9.0		5.3		3.4		3.0		2.7		
Wire size / max. length	#10 / 150ft																		

PEAK	7.5	13.7	20.0	7.9	10.0	7.1	9.2	5.8	8.0	4.8	6.9	3.7	4.2	2.9	4.1	2.3	3.3	1.6	2.3
SUN	6.0	12.2	17.2	6.5	8.5	5.8	7.7	5.0	7.1	4.0	4.9	2.6	3.7	2.3	3.2	1.9	2.6	1.5	2.0
hours/day	4.5	10.6	14.5	5.0	6.9	4.2	5.8	4.0	5.6	3.2	4.2	1.9	2.5	1.5	2.0	1.3	1.7	1.2	1.6
480 Wp	C-BF-04		HR-20				HR-14				HR-07				use HR-04 with #10/280ft		HR-04		
GPM	25.0		15.0		14.5		11.1		9.5		7.4		5.3		5.0		3.4		
Wire size / max. length	#10 / 130ft																		

PEAK	7.5	17.0	24.5	11.6	17.0	8.4	10.3	7.0	8.0	5.7	7.6	4.5	6.5	3.6	5.0	2.6	3.8	2.3	3.3
SUN	6.0	14.8	21.0	9.5	13.5	7.1	9.1	6.0	7.5	4.7	6.3	3.6	5.0	2.8	3.8	2.3	3.2	1.9	2.8
hours/day	4.5	12.7	17.4	7.4	10.0	5.8	7.9	5.0	6.6	3.7	5.0	2.6	3.6	2.1	2.6	1.9	2.5	1.6	2.3
660 Wp	C-BF-04		HR-20				HR-14				HR-07								
GPM	30.0		28.0		15.0		11.4		11.0		10.5		10.0		5.3		5.2		
Wire size / max. length	#10 / 85ft																		

PEAK	7.5	18.5	26.4	13.2	18.8	9.5	13.5	7.7	10.6	6.3	8.0	5.3	7.7	4.7	6.8	2.9	3.8	2.7	3.8
SUN	6.0	16.4	23.3	11.4	15.6	7.4	10.6	6.9	9.5	5.4	7.0	4.8	6.6	3.7	5.0	2.6	3.7	2.4	3.4
hours/day	4.5	14.0	20.0	9.3	12.4	5.3	7.4	6.1	8.5	4.5	6.0	4.1	5.6	2.4	3.2	2.4	3.3	2.1	2.9
720 Wp	C-BF-04		HR-20				HR-14				HR-07								
GPM	31.0		29.0		25.0		14.3		11.5		11.4		10.2		5.4		5.3		
Wire size / max. length	#10 / 85ft																		

PEAK	7.5	20.3	29.3	14.5	21.1	10.8	15.8	8.4	10.6	7.1	10.0	5.9	8.0	5.0	7.1	2.9	3.8	2.7	3.9
SUN	6.0	18.5	26.4	13.0	18.5	9.5	13.5	7.9	10.6	6.6	9.3	5.6	7.4	4.2	6.1	2.7	3.8	2.6	3.7
hours/day	4.5	16.6	23.3	11.4	15.6	7.9	10.8	7.4	10.0	6.1	8.2	4.8	6.3	3.4	4.8	2.5	3.5	2.4	3.4
840 Wp	C-DF-03		C-BF-04				HR-20				HR-14				HR-07				
GPM	43.0		32.0		29.5		14.5		14.2		11.4		10.3		5.4		5.3		
Wire size / max. length	#10 / 85ft																		

MORE WATER

BERNT LORENTZ GmbH & Co.KG
Hamburg, Germany
www.Lorentz.de

Table format is ©2002
DANKOFF SOLAR &
LORENTZ

System Voltage: 48 -72V
nominal, e.g. 4 to 6 standard
12V modules wired in series.
Voc 150Vmax.

LIFT LIMITS

These systems are selected for optimum performance. To allow unexpected drawdown, each system can handle an additional 15% lift.

HOW DAILY WATER VOLUME IS CALCULATED

Daily volume is calculated by integrating real flow vs. realistic solar (PV) output through the day. (peak sun hours/day = kWh/sq.m/day)

Calculations include a 10% PV output degradation (heat, dirt etc). Cable losses are included at maximum allowable length. The solar array is fixed at tilt angle = latitude of the location. For central USA, seasonal adjustment of the tilt angle increases daily volume by about 8% summer, 5% winter. Flow rates may vary +/- 10%.

Specifications are subject to change. Please use the newest version.

METRIC WIRE

nearest larger equivalent

AWG	mm ²
#18	1
#12	4
#10	6
#8	10
#6	16

PS600 SIZING TABLE for Solar Direct Systems

Ver: 05/01/10

Fixed and single axis tracked Systems



265 Feet 80m		300 Feet 90m		330 Feet 100m		400 Feet 120m		460 Feet 140m		530 Feet 160m		600 Feet 180m		660 Feet 200m		760 Feet 230m		VERTICAL LIFT
Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	Fixed	Tracked	

US Gallons x 1000 per day

0.85	1.25	0.70	1.10	0.65	1.00	0.60	0.90	0.50	0.72
0.68	0.97	0.55	0.83	0.48	0.71	0.43	0.62	0.34	0.49
0.50	0.68	0.40	0.55	0.30	0.41	0.25	0.34	0.18	0.25

HR-03

1.7	1.6	1.5	1.4	1.3
#10 / 330ft		#8 / 450ft		

1.00	1.35	0.90	1.32	0.85	1.24	0.79	1.14	0.71	1.06
0.87	1.16	0.79	1.06	0.71	1.03	0.66	0.87	0.53	0.77
0.74	1.00	0.69	0.92	0.58	0.79	0.45	0.61	0.34	0.48

HR-03

2.2	2.0	1.9	1.8	1.7
#10 / 330ft		#8 / 450ft		

1.24	1.82	1.19	1.42	1.06	1.32	0.98	1.32	0.79	1.11	0.61	0.85	0.45	0.63
1.02	1.44	0.98	1.24	0.85	1.10	0.79	1.08	0.66	0.91	0.53	0.71	0.36	0.50
0.79	1.06	0.77	1.03	0.63	0.87	0.61	0.85	0.53	0.71	0.45	0.58	0.26	0.37

HR-04H	HR-03				HR-03H			
2.5	2.1	2.0	1.9	1.8	1.6	1.4		
#10 / 330ft				#8 / 450ft				

1.51	2.17	1.45	2.11	1.32	1.85	1.19	1.72	0.87	1.19	0.74	1.06	0.61	0.79
1.27	1.77	1.16	1.72	1.00	1.40	0.90	1.27	0.79	1.06	0.63	0.87	0.50	0.66
1.03	1.37	0.87	1.19	0.69	0.92	0.58	0.79	0.69	0.92	0.50	0.66	0.40	0.53

HR-04H	HR-03				HR-03H			
3.2	3.0	2.7	2.5	1.9	1.7	1.5		
#6 / 420ft				#8 / 450ft				

2.11	3.04	1.72	2.30	1.45	2.06	1.35	1.96	1.19	1.69
1.72	2.44	1.45	1.96	1.29	1.76	1.07	1.53	0.92	1.31
1.32	1.85	1.19	1.59	1.14	1.45	0.79	1.11	0.66	0.92

HR-07	HR-04H			
5.0	3.4	3.3	3.2	3.1
#8 / 265ft				

2.5	3.6	2.3	3.3	1.59	2.30	1.51	2.17	1.40	1.85
2.2	3.0	2.0	2.8	1.53	2.11	1.32	1.80	1.16	1.59
1.9	2.5	1.6	2.1	1.45	1.96	1.06	1.43	0.92	1.24

HR-07	HR-04H			
5.2	5.0	3.3	3.3	3.2
#8 / 300ft				

2.6	3.7	2.5	3.6	1.8	2.0	1.7	2.0	1.59	1.98
2.4	3.2	2.2	3.1	1.6	1.8	1.5	1.7	1.37	1.85
2.1	2.8	1.9	2.6	1.4	1.7	1.3	1.6	1.16	1.59

HR-07	HR-04H			
5.2	5.0	3.3	3.3	3.2
#8 / 300ft				

INSTRUCTIONS
(1) Find the LIFT you require, and read the column below it.

Attention: WIRE SIZING \$\$\$
Especially for Lifts greater 100m / 330ft compare wire sizes with PS1200 system. Due to higher system voltage lots of \$ can be saved on the pump wire

More Lift ?
Choose PS1200 System for greater lift applications and lower cable cost

(2) Find the DAILY VOLUME you require. at 7.5 peak sun hrs/day at 6.0 peak sun hrs/day at 4.5 peak sun hrs/day (For more water, look further down the column.)

(3) Use the PEAK FLOW RATE for pipe sizing.

(4) Wire size / max. length (see below)

Daily solar radiation: 7.5 = moderately dry summer weather

PEAK SUN hours/day	7.5
	6.0
	4.5
300 Wp	
GPM	
Wire size/max. length	

PEAK SUN hours/day	7.5
	6.0
	4.5
350 Wp	
GPM	
Wire size/max. length	

PEAK SUN hours/day	7.5
	6.0
	4.5
420 Wp	
GPM	
Wire size/max. length	

PEAK SUN hours/day	7.5
	6.0
	4.5
480 Wp	
GPM	
Wire size/max. length	

PEAK SUN hours/day	7.5
	6.0
	4.5
660 Wp	
GPM	
Wire size/max. length	

PEAK SUN hours/day	7.5
	6.0
	4.5
720 Wp	
GPM	
Wire size/max. length	

PEAK SUN hours/day	7.5
	6.0
	4.5
840 Wp	
GPM	
Wire size/max. length	

M O R E W A T E R

Conversions for Flow:

1m³ / 0.003785 = US Gallons
1m³ / 0.004546 = Imp Gallons
LPM / 3.785 = US Gallon per minute
LPM / 4.546 = Imp Gallon per minute

Conversion for Lift / Length:

1m = 3.3ft

WIRE SIZES

Cable layout is calculated to stay within 5% power loss. Select PS1200 system to save \$ on cable !
PUMP CABLE, EXAMPLE: #10 / 250ft = maximum allowable length (controller to pump) for that wire size.

VARIATIONS

GREATER LENGTH: for each 150% increase, the next larger wire size is required.
SHORTER LENGTH: for each 33% decrease, the next smaller wire is allowed.

ARRAY TO CONTROLLER if <20 ft: #10min
CONTROLLER TO LOW-WATER PROBE: #18 min. 2-conductor
CONTROLLER TO FLOAT SWITCH: #18 min. 2-conductor

Battery Systems:

48V choose PS600 system
24-48V choose PS200 system

Pump Outlet Pipe Size	
HR-03H, 04H	1" NPT
HR-04, 07	1" NPT
HR-14, 20	1 1/4"
C-BF-04	1 1/2"
C-DF-03	2"